

VBA3200-100

700 - 3200MHz 100W Amplifier


- High reliability proven GaAs design
- Class A for maximum mismatch drive
- General linear power requirements



The **VBA3200-100** is a 700-3200MHz high power amplifier, designed primarily for EMC applications. It is based on our GaAs technology, offering the user the benefits of linearity, ruggedness and efficiency. With its compression point close to saturated output, it is equivalent to TWT amplifiers of twice the output power.

The amplifier operates in class A, the benefits for EMC applications being very low distortion and tolerance of 100% mismatch. Fold-back protection is neither fitted nor needed! This makes it supremely suited for very demanding antenna and test chamber requirements.

Performance Chart



Choose **GaAs Class A** for linearity, ruggedness, efficiency and cost.

See overleaf for technical specification

Electrical

Frequency Range (Instantaneous)	700-3200MHz
Output Power at 3dB Gain Compression	100W
Output Power at 1dB Gain Compression	80W
Gain	51dB Min
Third Order Intercept Point (see note 1)	60dBm
Gain variation with Frequency	±3dB
Harmonics at 80W Output Power	Better than -20dBc
Output Impedance	50 Ohms
Stability	Unconditional
Output VSWR Tolerance (see note 2)	Infinity:1
Input VSWR	2:1 (Max)
Supply Voltage	100-240V ac (+/- 10%)
Supply Frequency Range	45-63Hz
Supply Power	<1kVA (Max)
Mains Connector	IEC320

Mechanical

RF Connector Style	Type N female
Safety Interlock	Dual input, S/C and/or O/C to Mute
Communication Interface	USB/GPIB/Ethernet and front panel display
Dimensions	19 inch, 6U case, 500mm deep
Mass	25kg
Operating Temperature Range	0-40°C
Case Style Options	Rack mount with front or rear panel connectors Bench mount with front panel connectors

Regulatory Compliance

Conducted and Radiated Emissions	EN61326 Class A
Conducted and Radiated Immunity	EN61326:2013 Table 1
Safety	EN61010-1

Notes

- 1 The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.
- 2 Output VSWR tolerance is specified for excitation within the permitted levels and frequency range

**Represented Worldwide**

Vectawave Technology Ltd.
Unit D, The Apex,
St Cross Business Park, Monks Brook,
Newport, Isle of Wight, PO30 5XW

Tel: +44 (0) 1983 821 818

E-mail: sales@vectawave.co.uk